

FINISHING GUIDELINES

EXTERNAL JOINERY

Products taken out of their packaging must be fully decorated straight away. Sand away any handling marks or variations and dust thoroughly before priming or sealing. Ensure that wire wool or other sanding materials containing steel or iron are not used on any of our products. Where necessary it is important that doors and frames are fully sealed on the two faces and all edges.

Areas that are cut out for handles, locks, hinges, and letter plates etc. must also be fully sealed. These must be in accordance with British standards. Failure to seal products accordingly will invalidate any claims. Use a proprietary branded Hi-Build stain or paint and treat in accordance with the manufacturer's instructions. Note: Redwood, boarded doors including garage and Paint Grade doors are only suitable for Hi-Build paint finish. Lightly sand between coats to provide the best finish. Ensure adequate drying time is allowed between coats.

The sun can shorten darker colours' lifespan which makes them vulnerable to the elements. Where there are areas of high exposure, cover the external door with a hood, canopy or porch to help create a decorative finish and elongate your door's lifespan. Regular maintenance, however, is required to stop the deterioration of the wood, the construction and finish. When decorating the door, take care not to paint or stain weather strips, ironmongery, projecting hinges or moving parts as this could cause damage to the performance of the product. LPD external joinery is NOT suitable for varnishes, waxes, polishes, dyes, oils including Danish Oil, yacht varnish or lacquers, as the finishes do not protect our products.

MAINTENANCE GUIDELINES

LPD recommend the following points to maintain and extend the life of your exterior joinery products:

- All joinery products should be washed twice a year minimum with a mild solution of soapy water and rinsed with clean water. This should be completed at least four times if in a marine or industrial environment.
- All mechanical hinges etc. should be oiled with grease or neutral oils.
- Weather seals should be checked and cleaned often.
- When cleaned, scrape, lightly sand and touch up any areas of wear and tear with a matching microporous paint or stain. Bare wood should be primed first.
- Timber is a natural product so performs slightly differently throughout the year, seasonal adjustment may be required to assure ongoing performance.

INTERNAL JOINERY

Products taken out of their packaging, must be fully decorated straight away. Pre-finished doors however, come already finished and ready to hang. If the door edges are trimmed, they will need finishing with a polyurethane varnish. We recommend a Hi-Build, microporous product that is not quick drying to prevent waterlogging.

Our Oak timber doors can be decorated with a paint, stain, varnish or lacquer of your choice. White primed timber doors can be decorated with a good quality timber paint suited to your property.

LPD internal joinery is NOT suitable for waxes, polishes, dyes or oils. Please speak to the manufacturer of the product prior to use to ensure it is suitable for the style and construction of your veneered door.

LPD are forming a new partnership with Treatex and recommend their Hard Wax Oil for unfinished oak internal doors. It is designed to enhance and protect the natural beauty of your door and is user friendly, easy to apply and can be used in all interior situations.



RETURNS POLICY

Please note, wood is a natural product and therefore variants in the colour and grain is common. We suggest doors are purchased in plot orders to avoid batch variation. It is vital that you check the product before it is hung so issues can be resolved quickly and efficiently. Once a door is hung, this is deemed as acceptance and will not be liable for a return.